



POS-SC200

IMPORT MARKET GUATEMALA
www.importmarket.com.gt
Tel.: (502) 2286-9073 / 2286-7208 / 2286-6778
ventas@importmarket.com.gt
servicioalcliente@importmarket.com.gt



Description	Hands Free Omni-directional Barcode Scan
Color	Black
Height	156 mm
Width	100 mm
Depth	105 mm
Weight	300 g
Material	ABS + PC
Cable	Standard 2M straight
Scan Rate	1500 scans per second
Depth of field	0-200mm (UPC/EAN 100%, PCS=90%)
Interface	USB and RS232
Light Source	Visible laser Diode 650nm
Scan Pattern	20 lines Omni-directional
Scan Speed	1500 scan lines per second & 75 scan lines per second
Scan Precision	5mil
Visual Indicator	Two-color LED (blue, red)
Decode Capability	UPC/EAN/JAN, UPC-A & UPC-E, EAN-8 & EAN-13.JA-8 8, JAN-13.ISBN/ISSN, Code 39 (with full ASCII), Codabar (NW7), Code 128& EAN 128. Code 93. Interleaved 2 of 5
Print Contrast	30% @ UPC/EAN 100%
Voltage	5 V DC+/- 10%
Power consumption	1.0 watts
Operating current	270mA (Typical); 350mA (peak)
Laser Class	CDRH Class IIa; IEC 60825-1; Class 1
EMC	CE EN55022 B, FCC Part 15 Class B, VCCI, BSMI
Operating Temp.	0°C to 40°C
Storage Temp.	-20°C to - 60°C (-4°F to 140°F)
Humidity	5% to 95% (no dewing allowed)
Light Levels	0 to 100,000 Lux (daylight) 0 to 4,000 Lux (fluorescence)

